

BALETECH®

6460

Horizontal Baler

STANDARD FEATURES

- 1/2" Thick Full Sheet Construction
- Hydraulic Door Cylinder
- 25 HP Tri-Volt 3 Phase
- Guide Wire Tie Tracks
- Multiple Use Shear Blade
- High Efficiency Hydraulic Assembly with Regenerative Hydraulics
- Stroke Saver Cycle Feature
- Nema 4 Rated Enclosures
- Standard Hopper
- Full Weld Construction
- Large Feed Hopper
- Logic Controlled Operation
- Dual Level Photo Eyes

WARRANTY ONE (1) YEAR PARTS AND LABOR, THREE (3) YEARS ON THE STRUCTURE

BALE WEIGHTS

<u>OCC</u>	<u>Office Paper</u>	<u>News</u>	<u>Magazines</u>	<u>PET</u>
1600 Lbs. (737Kg) 1800 Lbs. (817 Kg)	1625 Lbs. (737 Kg)	1800 Lbs. (817 Kg) 2000 (907 Kg)	2000 Lbs. (907 Kg) 2400 (1088 Kg)	1000 Lbs (454 Kg)
<u>HDPE</u>	<u>Alum. Can</u>	<u>Misc N.F.</u>		
1000 Lbs (454 Kg) 1200 Lbs. (544 Kg)	800 Lbs. (363 Kg) 900 Lbs. (408 Kg)	1,200 Lbs. (544 Kg)		

STRUCTURAL

Hopper Opening	60" W x 84" L
Feed Chamber	60" W x 64"L
Chamber Floor	Full Sheet Construction -AR Lined-
Chamber Sidewalls	1/2" Thick Full Sheet Construction
Shipping Weight	25,500 Lbs. Shipping Weight(11,566 Kg)

SPECIFICATIONS

Main Cylinder	8" Bore x 120" Stroke x 5" Rod (20 cm) (304 cm) (12.7 cm)
Door Cylinder	4" Bore x 6" Stroke (10.2 cm) (15.2 cm)
Oil Reservoir	160 Gal (605 Liters)
Pump	43 Gal. Vane Pump (162 LPM)
Motor	TEFC 25 HP 208, 220, 480 Volts 3 Phase
Hyd. System Pressure	3,000 PSI (207 Bar)
Platen Force	150,800 Lbs.
Platen PSI	83 PSI. (6.0 Bar)
Cycle Time Adjustable	30 Sec - 18 Sec Stoke Saver
Bale Size	60 x 30 x 48

PERFORMANCE DATA

DIMENSIONS

	<u>HEIGHT</u>	<u>WIDTH</u>	<u>LENGTH</u>
Frame	57" (145 cm)	6' 5" (198 cm)	25 Ft (762 cm)
W/ Standard Feed Hopper	87" (221 cm)		

OPTIONAL FEATURES

- Bob Cat Feed Hopper
- Conveyor Feed Hopper
- Maintenance Program Available
- Conveyor Control Package
- Custom Colors
- Thermal Oil Heater

www.balettech.com

Distributed By :